
(19) World Intellectual Property Organization

International Bureau







PCT

(10) International Publication Number WO 2005/012811 A1

(51) International Patent Classification7:

F25B 49/00

(21) International Application Number:

PCT/KR2003/001635

- (22) International Filing Date: 13 August 2003 (13.08.2003)
- (25) Filing Language:

Korean

(26) Publication Language:

English

- (30) Priority Data: 10-2003-0052247
- 29 July 2003 (29.07.2003) KR
- (71) Applicant (for all designated States except US): METACHEM INC. [KR/KR]; 108-1 Gangdeok-ri, Miyang-myeon, Anseong-si, Gyeonggi-do 456-842 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LEE, Deok-Jae [KR/KR]; 301-1804, Howongarden Apt., 376, Howon-dong, Uijeongbu-si, Gyeonggi-do 480-711 (KR).
- (74) Agents: LEE, Bong-Jin et al., 1610 Hyundai Venturetel, 642-1, Yeoksam 1-dong, Gangnam-gu, Seoul 135-910 (KR).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OIL CHECKING DEVICE FOR COMPRESSOR OF AIR CONDITIONING SYSTEM



(57) Abstract: An oil checking device for compressor of air conditioning system includes an oil container connected to an high-pressure part of the air conditioning system to receive refrigerant and oil from the high-pressure part, the oil container being formed of a transparent material so that a user can observe the oil mixed with the refrigerant, a valve member for selectively opening a gas line and a liquid line respectively connected to upper-inner and lower-inner portions of the oil container to exhaust refrigerant gas and compressor oil from the oil container to a low-pressure part of the air conditioning system, a ball floater disposed in the oil container, and an oil amount/state display part formed on the oil container, the oil amount/state display part having a reference oil level that can be compared with the compressor oil.

05/012811 A1